

FLOS

03.4572.GL Gold

Kap 105 Square

Designed by FLOS Architectural, 2013



Recessed 12V lamp luminaire. Remote transformer not included.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	QR-CBC 51
Lamp holders	GX5.3
Number of lamps	1

Physical

Colour	Gold
Trim	No
Orientation	Fixed
Recessed depth (mm)	185
Net weight (kg)	0.55
Package height (mm)	170
Package width (mm)	235
Package length (mm)	200
IP internal	20



Download

[Mounting instructions](#) PDF

[Item information](#) JPG

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



Schematic light drawing



Beam Angle: 46°


h(m)	E(lx)	D(m)
1	655	0.84
2	164	1.69
3	73	2.53
4	41	3.37
5	26	4.21

Ecodesign and Energy

Labelling



Replaceable (LED only)
light source by an end-
user



Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric


Electrical

Insulation class	III
Forward voltage (V)	12
Power supply	Remote excluded

Notes

Check your lamp dimensions to match the product.

Accessories & Power Supply



REQUIRED
Accessory

Installation

08.8479.00

Installation frame No Trim