

FLOS

03.4236.B1 White

Kap Ø 80 Adjustable

Designed by FLOS Architectural, 2016



Recessed 12V lamp luminaire. Remote transformer not included.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED retrofit
Lamp type	QR-CBC 51
Lamp holders	GX5.3
Ilcos	No
Number of heads	1

Physical

Colour	White
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Recessed depth (mm)	120
Spot diameter (mm)	74
Net weight (kg)	0.12
IP internal	20
IP external	23



Download


Mounting instructions

[↓ PDF](#)

Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



Replaceable control gear by a professional



Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	III
Frequency (Hz)	0
Main voltage (Vac)	12
Forward voltage (V)	12
LED current (mA)	-9
Driver	Remote excluded
Dimmable	No
Dimming type	Electronic 12V
Emergency type	No

Notes

Not suitable for lens accessories.

Accessories & Power Supply

Max. \varnothing 123



\varnothing 93



REQUIRED
Frame

Installation

08.9102.00

Installation frame No Trim

REQUIRED
Power supply

Electrical

60.9424

12V Electronic Transformer 35-105W



REQUIRED
Power supply

Electrical

60.9398

12V Electronic Transformer 20-70W

