

FLOS

03.4236.GL Gold

Kap Ø 80 Adjustable

Designed by FLOS Architectural, 2016



Recessed 12V lamp luminaire. Remote transformer not included.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED retrofit
Lamp type	QR-CBC 51
Lamp holders	GX5.3
Ilcos	No
Number of heads	1

Physical

Colour	Gold
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Recessed depth (mm)	120
Spot diameter (mm)	74
Net weight (kg)	0.12
IP internal	20
IP external	23



Download


Mounting instructions



Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



Replaceable control gear by a professional



Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	III
Frequency (Hz)	0
Main voltage (Vac)	12
Forward voltage (V)	12
LED current (mA)	-9
Driver	Remote excluded
Dimmable	No
Dimming type	Electronic 12V
Emergency type	No

Notes

Not suitable for lens accessories.

Accessories & Power Supply

Max. \varnothing 123



\varnothing 93



REQUIRED
Frame

Installation

08.9102.00

Installation frame No Trim

REQUIRED
Power supply

Electrical

60.9424

12V Electronic Transformer 35-105W

REQUIRED
Power supply

Electrical

60.9398

12V Electronic Transformer 20-70W