

03.4185.B1.UQ White

## Kap Ø 80 Adjustable Optic Medium - Non IC


Designed by FLOS Architectural, 2016



Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | LED array           |
| Number of lamps        | 1                   |
| Power (W)              | 9.2                 |
| Source flux (lm)       | 908                 |
| System flux (lm)       | 664                 |
| Efficacy (lm/W)        | 72                  |

### Physical

|                          |            |
|--------------------------|------------|
| Color                    | White      |
| Trim                     | Yes        |
| Orientation              | Adjustable |
| Rotation (°)             | 360        |
| Longitudinal tilting (°) | 20         |
| Transversal tilting (°)  | 20         |
| Net weight (lb)          | 7.77       |
| IP internal              | 20         |
| IP external              | 54         |

### Download

[Family spec sheet](#) [ZIP](#)


[Mounting instructions](#) [PDF](#)

### Photometric Files

[LDT / IES](#) [ZIP](#)



Schematic light drawing



Photometric

|                          |                          |
|--------------------------|--------------------------|
| Lighting type            | Direct                   |
| Light distribution       | Symmetric                |
| CCT (K)                  | 2700                     |
| CRI>                     | 90                       |
| McAdam steps (SDCM)      | 3                        |
| LED Life / Failure Ratio | L80B50>50.000h (Tc=85°C= |
| Beam angle C0-180 (°)    | 26                       |
| Beam angle C90-270 (°)   | 26                       |

Electrical

|                     |      |
|---------------------|------|
| Insulation class    | III  |
| Forward voltage (V) | 18.4 |
| LED current (mA)    | 500  |

Notes

Diffusing lens included.

Accessories & Power Supply

Max. ø123




REQUIRED  
Frame

Installation

08.9102.00


Installation frame No Trim



REQUIRED  
Power supply

SP14W500MA-ELV-E01

Splice Box 9"x2"x1.5", 500mA ,  
14W, ELV Dimmable, Thermal  
120V




REQUIRED  
Power supply

Electrical

SP20W500MA-277-V01

Splice Box 9" x 2" x 1.5", 500mA,  
20W, 0-10V, 277V




REQUIRED  
Power supply

Electrical

SP14W500MA-120-V01

Splice Box 14W, 1% dim, 0-10V,  
120V.



OPTIONAL  
Housing and Hanger Bar

TRAY-0016

Registration Tray - non electrical,  
place holder for non IC new  
construction Round, Ø4"