

03.4180.B1.UQ White

Kap Ø 80 Fixed Optic Medium - Non IC


Designed by FLOS Architectural, 2016



Recessed luminaire with LED light source. Power supply not included. Diffusing lens included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	9.2
Source flux (lm)	956
System flux (lm)	630
Efficacy (lm/W)	68

Physical

Color	White
Trim	Yes
Orientation	Fixed
Net weight (lb)	7.77
IP internal	20
IP external	54

Download

[Family spec sheet](#) [ZIP](#)


[Mounting instructions](#) [PDF](#)

Photometric Files

[LDT / IES](#) [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C=
Beam angle C0-180 (°)	26
Beam angle C90-270 (°)	26

Electrical


Insulation class	III
Forward voltage (V)	18.4
LED current (mA)	500

Notes

Diffusing lens included.

Accessories & Power Supply

Max. ø123




REQUIRED
Frame

Installation

08.9102.00


Installation frame No Trim



REQUIRED
Power supply

SP14W500MA-ELV-E01

Splice Box 9"x2"x1.5", 500mA ,
14W, ELV Dimmable, Thermal
120V




REQUIRED
Power supply

Electrical

SP20W500MA-277-V01

Splice Box 9" x 2" x 1.5", 500mA,
20W, 0-10V, 277V




REQUIRED
Power supply

Electrical

SP14W500MA-120-V01

Splice Box 14W, 1% dim, 0-10V,
120V.



OPTIONAL
Housing and Hanger Bar

TRAY-0016

Registration Tray - non electrical,
place holder for non IC new
construction Round, Ø4"