

Kap 80 Square Adjustable

Designed by FLOS Architectural, 2016



Recessed luminaire with main voltage source.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	PAR16
Lamp holders	GZ10
Number of lamps	1

Physical

Colour	Black
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Recessed depth (mm)	155
Net weight (kg)	0.12
Package height (mm)	90
Package width (mm)	140
Package length (mm)	105
IP internal	20
IP external	23



Download

Mounting instructions [↓ PDF](#)
Item information [↓ JPG](#)

Ecodesign and Energy Labelling



Replaceable (LED only)
light source by an end-user



Photometric

Lighting type	Direct
Light distribution	Symmetric


Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Forward voltage (V)	230

Notes

Not suitable for lens accessories.

Accessories & Power Supply



REQUIRED
Frame

Installation

08.9103.00

Installation frame No Trim