

## Kap 80 Square Adjustable

Designed by FLOS Architectural, 2016



Recessed luminaire with main voltage source.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | Bulb                |
| Light sources included | no                  |
| Lamp category          | LED retrofit        |
| Lamp type              | PAR16               |
| Lamp holders           | GZ10                |
| Number of lamps        | 1                   |

### Physical

|                          |            |
|--------------------------|------------|
| Colour                   | Gold       |
| Trim                     | No         |
| Orientation              | Adjustable |
| Rotation (°)             | 360        |
| Longitudinal tilting (°) | 20         |
| Transversal tilting (°)  | 20         |
| Recessed depth (mm)      | 155        |
| Net weight (kg)          | 0.12       |
| Package height (mm)      | 90         |
| Package width (mm)       | 140        |
| Package length (mm)      | 105        |
| IP internal              | 20         |
| IP external              | 23         |



### Download

Mounting instructions [↓ PDF](#)  
Item information [↓ JPG](#)

### Ecodesign and Energy Labelling



Replaceable (LED only)  
light source by an end-user



Photometric

|                    |           |
|--------------------|-----------|
| Lighting type      | Direct    |
| Light distribution | Symmetric |

Electrical

|                     |         |
|---------------------|---------|
| Insulation class    | II      |
| Frequency (Hz)      | 50/60   |
| Main voltage (Vac)  | 220-240 |
| Forward voltage (V) | 230     |

Notes

Not suitable for lens accessories.

Accessories & Power Supply



REQUIRED  
Frame

Installation

08.9103.00

Installation frame No Trim