


03.4243.B1 White

## Kap 80 Square Wall-Washer

Designed by FLOS Architectural, 2016



Recessed luminaire with main voltage source.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | Bulb                |
| Light sources included | no                  |
| Lamp category          | LED retrofit        |
| Lamp type              | PAR16               |
| Lamp holders           | GU10                |
| Number of lamps        | 1                   |

### Physical

|                     |       |
|---------------------|-------|
| Colour              | White |
| Trim                | No    |
| Orientation         | Fixed |
| Recessed depth (mm) | 140   |
| Net weight (kg)     | 0.12  |
| Package height (mm) | 90    |
| Package width (mm)  | 140   |
| Package length (mm) | 105   |
| IP internal         | 20    |
| IP external         | 23    |



### Download

Mounting instructions [↓ PDF](#)  
Item information [↓ JPG](#)

### Ecodesign and Energy Labelling



Replaceable (LED only)  
light source by an end-user



Photometric

|                    |                  |
|--------------------|------------------|
| Lighting type      | Indirect, Direct |
| Light distribution | Asymmetric       |

Electrical

|                     |         |
|---------------------|---------|
| Insulation class    | II      |
| Frequency (Hz)      | 50/60   |
| Main voltage (Vac)  | 220-240 |
| Forward voltage (V) | 230     |

Notes

Not suitable for lens accessories.

Accessories & Power Supply



REQUIRED  
Frame

Installation

08.9103.00

Installation frame No Trim