


Kap 80 Surface Round Mains Dimming Optic Flood

Designed by FLOS Architectural, 2017



Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling surface
Enviroment	Indoor dry location
LED type	LED array
Lamp category	LED
Ilcos	No
Number of heads	1
Power (W)	9.2
Source flux (lm)	745
System flux (lm)	649

Physical

Colour	Black/Copper
Trim	No
Orientation	Fixed
Net weight (kg)	0.45
IP internal	20
IP external	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	45

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	18.20
Driver	Integrated
Dimmable	Yes
Dimming type	Mains Cut Dimming
Emergency type	No

Notes

There may be a 10% variation in the minimum dimming point between different luminaires.