

## Kap 80 Surface Square Optic Flood

Designed by FLOS Architectural, 2017




LED - LED array - 9.2W - 704lm - 2700K - CRI> 90 - Beam° 53

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Non dimmable 110/240V.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | LED array           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 9.2                 |
| System power (W)       | 11.3                |
| Source flux (lm)       | 908                 |
| Lumen Output (lm)      | 704                 |

### Physical

|                     |                 |
|---------------------|-----------------|
| Colour              | Deep Brown/Gold |
| Trim                | No              |
| Orientation         | Fixed           |
| Length (mm)         | 80              |
| Net weight (kg)     | 0.45            |
| Package height (mm) | 190             |
| Package width (mm)  | 220             |
| Package length (mm) | 175             |
| IP internal         | 20              |

### Download

|                       |                              |
|-----------------------|------------------------------|
| Mounting instructions | <a href="#">Download PDF</a> |
| Item information      | <a href="#">Download JPG</a> |

### Photometric Files


|           |                              |
|-----------|------------------------------|
| LDT / IES | <a href="#">Download ZIP</a> |
|-----------|------------------------------|

### Technical Drawings

|    |                              |
|----|------------------------------|
| 2D | <a href="#">Download ZIP</a> |
| 3D | <a href="#">Download ZIP</a> |



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| McAdam steps (SDCM)    | 3         |
| Beam angle C0-180 (°)  | 53        |
| Beam angle C90-270 (°) | 53        |
| UGR <sub>L</sub>       | <16       |

Electrical

|                     |              |
|---------------------|--------------|
| Insulation class    | I            |
| Frequency (Hz)      | 50/60        |
| Main voltage (Vac)  | 220-240      |
| Forward voltage (V) | 18.2         |
| Power supply        | Integrated   |
| Dimmable            | No           |
| Power supply type   | Non Dimmable |