

Kap 80 Surface Square Optic Flood Dali/Push Version

Designed by FLOS Architectural, 2017




LED - LED array - 11,3W - 704lm - 2700K - CRI> 90 - Beam° 53

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Dali/Push dimming 220/240V.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
LED type	LED array
Lamp category	LED
Ilcos	No
Number of lamps	1
Power (W)	11,3
Source flux (lm)	908
Lumen Output (lm)	704

Physical

Colour	Deep Brown/Gold
Trim	No
Orientation	Fixed
Net weight (kg)	0.45
IP internal	20
IP external	20

Download

Mounting instructions	↓ PDF
Item information	↓ JPG


Photometric Files

LDT / IES	↓ ZIP
-----------	-------

Technical Drawings

2D	↓ ZIP
3D	↓ ZIP

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	53
Beam angle C90-270 (°)	54

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	18.20
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable Push, Dimmable DALI 1
Emergency	No