

FLOS

03.4244.74 Black

Kap Ø 80 Wall-Washer


Designed by FLOS Architectural, 2016



Recessed 12V lamp luminaire. Remote transformer not included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED retrofit
Lamp type	QR-CBC 51
Lamp holders	GX5.3
Ilcos	No
Number of heads	1
System flux (lm)	733

Physical

Colour	Black
Trim	No
Orientation	Fixed
Recessed depth (mm)	130
Spot diameter (mm)	74
Net weight (kg)	0.12
IP internal	20
IP external	23

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric
Beam angle C0-180 (°)	20
Beam angle C90-270 (°)	20


Electrical

Insulation class	II
Frequency (Hz)	0
Main voltage (Vac)	12
Forward voltage (V)	12
LED current (mA)	-9
Driver	Remote excluded
Dimmable	No
Dimming type	Electronic 12V
Emergency type	No

Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



Replaceable control gear by a professional

Notes

Not suitable for lens accessories.

Accessories & Power Supply

Max. \varnothing 123



\varnothing 93



REQUIRED
Frame

Installation

08.9102.00

Installation frame No Trim

REQUIRED
Power supply

Electrical

60.9424

12V Electronic Transformer 35-105W

REQUIRED
Power supply

Electrical

60.9398

12V Electronic Transformer 20-70W