

# FLOS

03.4245.B1 White

## Kap Ø 80 Wall-Washer

Designed by FLOS Architectural, 2016



Recessed luminaire with main voltage source.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED retrofit
Lamp type	PAR16
Lamp holders	GU10
Ilcos	No
Number of heads	1
System power (W)	50

### Physical

Colour	White
Trim	No
Orientation	Fixed
Recessed depth (mm)	140
Spot diameter (mm)	74
Net weight (kg)	0.12
IP internal	20
IP external	23



### Download

Mounting instructions

[↓ PDF](#)

### Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



## Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric

## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	230
Forward voltage (V)	230
LED current (mA)	-9
Emergency type	No

## Notes

Not suitable for lens accessories.

---

## Accessories & Power Supply

Max.  $\varnothing$ 123



$\varnothing$ 93



REQUIRED  
Frame

Installation

08.9102.00

Installation frame No Trim

REQUIRED  
Power supply

Electrical

60.9424

12V Electronic Transformer 35-105W

REQUIRED  
Power supply

Electrical

60.9398

12V Electronic Transformer 20-70W