

FLOS

03.4245.GL Gold

Kap Ø 80 Wall-Washer

Designed by FLOS Architectural, 2016



Recessed luminaire with main voltage source.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED retrofit
Lamp type	PAR16
Lamp holders	GU10
Ilcos	No
Number of heads	1
System power (W)	50

Physical

Colour	Gold
Trim	No
Orientation	Fixed
Recessed depth (mm)	140
Spot diameter (mm)	74
Net weight (kg)	0.12
IP internal	20
IP external	23



Download

Mounting instructions

[↓ PDF](#)

Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	230
Forward voltage (V)	230
LED current (mA)	-9
Emergency type	No

Notes

Not suitable for lens accessories.

Accessories & Power Supply

Max. \varnothing 123



\varnothing 93



REQUIRED
Frame

Installation

08.9102.00

Installation frame No Trim

REQUIRED
Power supply

Electrical

60.9424

12V Electronic Transformer 35-105W



REQUIRED
Power supply

Electrical

60.9398

12V Electronic Transformer 20-70W

