

# FLOS



03.5733.B3B Brown/Black

## Kap Surface Wall Ø 100

Designed by FLOS Architectural, 2020




LED - Power LED - 9W - 413lm - 3000K - CRI> 80 - Beam° 28

Luminaire for wall mounting with led light source. nonregulable 110/240V, 50-60hz power supply integrated in luminaire body.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                  |                     |
|------------------|---------------------|
| Mounting         | Wall surface        |
| Environments     | Indoor dry location |
| LED type         | Power LED           |
| Lamp category    | LED                 |
| Number of heads  | 1                   |
| Power (W)        | 9                   |
| System power (W) | 11W                 |
| Source flux (lm) | 1000                |
| System flux (lm) | 413                 |

### Physical

|                     |             |
|---------------------|-------------|
| Colour              | Brown/Black |
| Orientation         | Fixed       |
| Spot diameter (mm)  | 100         |
| Length (mm)         | 100         |
| Net weight (kg)     | 1.58        |
| Package height (mm) | 21          |
| Package width (mm)  | 22          |
| Package length (mm) | 34          |
| IP internal         | 20          |
| IP external         | 20          |

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



## Schematic light drawing



### Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 28        |
| Beam angle C90-270 (°) | 28        |

### Electrical

|                    |              |
|--------------------|--------------|
| Insulation class   | I            |
| Frequency (Hz)     | 50/60        |
| Main voltage (Vac) | 110/240      |
| Driver             | Integrated   |
| Dimmable           | No           |
| Dimming type       | Non Dimmable |
| Emergency type     | No           |