



F002A21AU71.A Anodized Black

Klein Pro H 600 mm Non Dimmable Anodized


Designed by FLOS Outdoor, 2017



Power supply not included. Solid surface or ground installation accessories to be ordered separately. Each luminaire is equipped with 1000 mm lenght outgoing cable and a wiring kit.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

RG 1

0

EAN	8054793178592	
Mounting	Ground	
Environments	Outdoor wet location	
Light Source Type	LED	
Light sources included	Yes	
LED type	Power LED	
Number of lamps	1	
System power (W)	8.4	
System flux (lm)	99	

ΙK

Physical

Color	Anodized Black	
Orientation	Fixed	
Net weight (lb)	3.57	
Package height (in)	4.72	
Package width (in)	32.76	
Package length (in)	4.53	
Package volume (in)	700.68	
IP internal	66	

Download

Family spec sheet	$\overline{7}$	ZII
Mounting instructions	$\overline{\mathbf{A}}$	ZII

Photometric Files

LDT / IES



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E





Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

https://professional.flos.com/en-US/us/product/klein-pro-h-600-mm-non-dimmable-anodized-black-f002a21au71.a/

F002A21AU71.A

Schematic light drawing



Beam	Beam Angle:	
h(m)	E(lx)	D(m)
1	332	0.97
2	83	1.93
3	37	2.90
4	21	3.87
5	13	4.83

Photometric

Light distribution	Asymmetric
CCT (K)	2700
CRI>	80
Beam angle CO-180 (°)	45
Beam angle C90-270 (°)	20
Extreme cut off	No

Electrical

Frequency (Hz)	50/60
Driver	Integrated
Dimmable	No
Dimming interface	Not Dimmable

Notes

Carefully install and maintain the fixtures to avoid damaging the coating. For LED fixtures, most problems are tied to electrical issues related to the insulation, which may cause destructive electrical discharges. These are frequently caused by:

- power surges from the power network where fixture is connected.
- electrostatic discharge (ESD) from the environment.

We recommend installing a power-surge protection device on the fixture to reduce the intensity of these effects and prevent irreversible damages. The specific device should be chosen based on the electrical characteristics.

Accessories & Power Supply



OPTIONAL Accessory

F002704007

Anodized aestetical pole screen Anodized Black



OPTIONAL Accessory

F002Z020000

Klein Pro base plate and fixing bolts 85x85xH160 mm



OPTIONAL Accessory

F002Z010001.A

Fixing base for solid surfaces White



OPTIONAL Accessory

F002Z010006.A

Fixing base for solid surfaces Grey



OPTIONAL Accessory

F002Z010030.A

Fixing base for solid surfaces Black



OPTIONAL Accessory

F002Z010012.A

Fixing base for solid surfaces Forest Green



OPTIONAL Accessory

F990F00A000

S.P.D. (SURGE PROTECTION DEVICE)



OPTIONAL Accessory

F002Z030000.A

Minimal Klein Pro ground fixation plate, 47x57xH160 mm



OPTIONAL Accessory

F002Z010018.A

Fixing base for solid surfaces Deep Brown