

FLOS

F002A30AU06.A Grey

Klein Pro H 600 mm Non Dimmable Grey

Designed by FLOS Outdoor, 2017



Power supply not included. Solid surface or ground installation accessories to be ordered separately. Each luminaire is equipped with 1000 mm length outgoing cable and a wiring kit.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793179490
Mounting	Ground
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	11
System flux (lm)	103

Physical


Color	Grey
Orientation	Fixed
Net weight (lb)	3.57
Package height (in)	4.72
Package width (in)	32.76
Package length (in)	4.53
Package volume (in)	700.68
IP internal	66

Download

Family spec sheet	ZIP
Mounting instructions	ZIP


Photometric Files

LDT / IES	ZIP
-----------	-----



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



<https://professional.flos.com/en-US/us/product/klein-pro-h-600-mm-non-dimmable-grey-f002a30au06.a/>


F002A30AU06.A

©2022 Flos - P.IVA 00290820174 - 8/28/2025

professional.flos.com | flos.outdoor@flos.com 1/3

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Photometric

Light distribution	Asymmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	20
Extreme cut off	No

Electrical

Frequency (Hz)	50/60
Driver	Integrated
Dimmable	No
Dimming interface	Not Dimmable

Notes

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating. Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection. For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges. These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

Accessories & Power Supply



OPTIONAL
Accessory

F002Z040070

Anodized aestetical pole screen
Anodized Natural



OPTIONAL
Accessory

F002Z040071

Anodized aestetical pole screen
Anodized Black



OPTIONAL
Accessory

F002Z040073

Anodized aestetical pole screen
Anodized Gold



OPTIONAL
Accessory

F002Z020000


Klein Pro base plate and fixing
bolts 85x85xH160 mm



OPTIONAL
Accessory

F002Z010006.A

Fixing base for solid surfaces
Grey



OPTIONAL
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION
DEVICE)



OPTIONAL
Accessory

F002Z030000.A

Minimal Klein Pro ground fixation
plate, 47x57xH160 mm