




F002B21D071.B Anodized Black


# Klein Pro H 900 mm Dali Anodized Black

Designed by FLOS Outdoor, 2017



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



## Main specifications

EAN	8054793182230
Mounting	Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	11
Lumen Output (lm)	292

## Physical

Colour	Anodized Black
Trim	No
Orientation	Fixed
Net weight (kg)	2.16
Package height (mm)	117
Package width (mm)	1010
Package length (mm)	115
Package volume (m3)	0.01
IP internal	66

# Download

Mounting instructions



## Photometric Files

LDT / IES



# **Technical Drawings**

2D	<b>⊥</b> ZIP
3D	<b>⊥</b> ZIP
₽Bim	. <b>↓</b> . 7IP













https://professional.flos.com/en/global/product/klein-pro-h-900-mm-dali-anodized-black-f002b21d071.b/

F002B21D071.B

## Schematic light drawing



Beam Angle:		41
h(m)	E(lx)	D(m
1	332	0.9
2	83	1.9
3	37	2.9
4	21	3.8
5	13	4.8

## Photometric

Light distribution	Asymmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	20
Extreme cut off	No

#### Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Power supply type	Dimmable DALL 1
	DITITIONE DALI I
Dimming interface	Dimmer Integrated

# Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **E** 



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

#### **Notes**

Carefully install and maintain the fixtures to avoid damaging the coating. For LED fixtures, most problems are tied to electrical issues related to the insulation, which may cause destructive electrical discharges.

These are frequently caused by:

- power surges from the power network where fixture is connected.
- electrostatic discharge (ESD) from the environment.

We recommend installing a power-surge protection device on the fixture to reduce the intensity of these effects and prevent irreversible damages. The specific device should be chosen based on the electrical characteristics.

## **Accessories & Power Supply**



OPTIONAL Accessory

F002Z050071

Anodized aestetical pole screen Anodized Black



OPTIONAL Accessory

F002Z020000

Klein Pro base plate and fixing bolts 85x85xH160 mm



## OPTIONAL Accessory

F002Z010001.A

Fixing base for solid surfaces White



### OPTIONAL Accessory

F002Z010006.A

Fixing base for solid surfaces Grey



## OPTIONAL Accessory

F002Z010030.A

Fixing base for solid surfaces Black



# OPTIONAL Accessory

F002Z010012.A

Fixing base for solid surfaces Forest Green



# OPTIONAL Accessory

F990F00A000

S.P.D. (SURGE PROTECTION DEVICE)



## OPTIONAL Accessory

F002Z030000.A

Minimal Klein Pro ground fixation plate, 47x57xH160 mm



## OPTIONAL Accessory

F002Z010018.A

Fixing base for solid surfaces Deep Brown