

FLOS

 F002B40B018.B Deep Brown

Klein Pro H 900 mm Dimmable 1-10V Deep Brown


Designed by FLOS Outdoor, 2017



220-240V power supply integrated. Solid surface or ground installation accessories to be ordered separately. Each luminaire is equipped with 1000 mm lenght outgoing cable and a wiring kit.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793183749
Mounting	Ground
Environments	Outdoor wet location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	11
Lumen Output (lm)	325

Physical

Colour	Deep Brown
Trim	No
Orientation	Fixed
Net weight (kg)	2.16
Package height (mm)	117
Package width (mm)	1010
Package length (mm)	115
Package volume (m3)	0.01
IP internal	66

Download

Mounting instructions  ZIP

Photometric Files

LDT / IES  ZIP

Technical Drawings


2D  ZIP

3D  ZIP

 Bim  ZIP



Schematic light drawing



Photometric


Light distribution	Asymmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	20
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Integrated
Dimmable	Yes
Dimming interface	Dimmer Integrated
Emergency	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Notes

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating. Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection. For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges. These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

Accessories & Power Supply



OPTIONAL
Accessory

F002Z050070
Anodized aestetical pole screen
Anodized Natural



OPTIONAL
Accessory

F002Z050071
Anodized aestetical pole screen
Anodized Black




OPTIONAL
Accessory

F002Z050073
Anodized aestetical pole screen
Anodized Gold



OPTIONAL
Accessory

F002Z020000
Klein Pro base plate and fixing
bolts 85x85xH160 mm



OPTIONAL
Accessory

F990E00A000
S.P.D. (SURGE PROTECTION
DEVICE)



OPTIONAL
Accessory

F002Z030000.A
Minimal Klein Pro ground fixation
plate, 47x57xH160 mm



OPTIONAL
Accessory

F002Z010018.A
Fixing base for solid surfaces
Deep Brown