



F002B30AU12.A Forest Green


Klein Pro H 900 mm Non Dimmable Forest Green

Designed by FLOS Outdoor, 2017

Power supply not included. Solid surface or ground installation accessories to be ordered separately. Each luminaire is equipped with 1000 mm lenght outgoing cable and a wiring kit.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

RG 1

0

EAN	8054793182636	
Mounting	Ground	
Environments	Outdoor wet location	
Light Source Type	LED	
Light sources included	Yes	
LED type	Power LED	
Number of lamps	of lamps 1	
System power (W)	11	
System flux (lm)	103	

ΙK

Physical

Color	Forest Green
Orientation	Fixed
Net weight (lb)	4.76
Package height (in)	4.61
Package width (in)	39.76
Package length (in)	4.53
Package volume (in)	829.32
IP internal	66

Download

Family spec sheet	$\overline{\uparrow}$	ZIF
Mounting instructions	业	ZIF

Photometric Files

LDT / IES



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E





Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

https://professional.flos.com/en-US/us/product/klein-pro-h-900-mm-non-dimmable-forest-green-f002b30au12.a/

F002B30AU12.A

Schematic light drawing



Beam	Angle:	41°
h(m)	E(lx)	D(m)
1	343	0.97
2	86	1.93
3	38	2.90
4	21	3.87
5	14	4.83

Photometric

Light distribution	Asymmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	20
Extreme cut off	No

Electrical

Frequency (Hz)	50/60
Driver	Integrated
Dimmable	No
Dimming interface	Not Dimmable

Notes

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

Accessories & Power Supply



OPTIONAL Accessory

F002Z050070

Anodized aestetical pole screen Anodized Natural



OPTIONAL Accessory

F002Z050071

Anodized aestetical pole screen Anodized Black



OPTIONAL Accessory

F002Z050073

Anodized aestetical pole screen Anodized Gold



OPTIONAL Accessory

F002Z020000

Klein Pro base plate and fixing bolts 85x85xH160 mm



OPTIONAL Accessory

F002Z010012.A

Fixing base for solid surfaces Forest Green



OPTIONAL Accessory

F990F00A000

S.P.D. (SURGE PROTECTION DEVICE)



OPTIONAL Accessory

F002Z030000.A

Minimal Klein Pro ground fixation plate, 47x57xH160 mm