

FLOS

03.3922.30E White

LED Curtain 600 mm UPGRADE

Designed by FLOS Architectural, 2016



Recessed luminaire for direct lighting with LED. Elliptical lens 12°x52° incorporated.
Remote transformer not included

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Power (W)	17.3
Source flux (lm)	2097
Lumen Output (lm)	1024

Physical

Colour	White
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	42
Length (mm)	600
Net weight (kg)	0.6
Package volume (m3)	0.01
IP internal	20



Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)




IP

20

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **G**

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
Beam angle C0-180 (°)	12
Beam angle C90-270 (°)	12
Extreme cut off	No

Electrical

Insulation class	III
Frequency (Hz)	50/60
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable 1-10V, Dimmable DALI 1

Notes

12 LEDs.

Accessories & Power Supply



REQUIRED
Power supply
Electrical

60.8515
Electronic transformer with constant voltage (24V) for LED. 60W. 100/240V. For independent use



REQUIRED
Power supply
Electrical

60.9089
Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W



REQUIRED
Power supply
Electrical

60.9407
Electronic transformer with constant voltage (24V) for LED. 100/240V. 120W



REQUIRED
Power supply
Electrical

60.8703
Electronic transformer with constant voltage (24V) for LED. 100/240V. 25W



REQUIRED
Accessory
06.1034.00

Power cable L: 500 mm



REQUIRED
Accessory
Electrical

60.8640
Control Unit 1-10V



REQUIRED
Accessory
Electrical

60.9766
Control Unit DALI



OPTIONAL
Accessory
06.1032.00

Connection cable L: 100 mm



OPTIONAL
Accessory

06.1033.00

Connection cable L: 500 mm