

FLOS

03.3923.30E White

LED Curtain 900 mm UPGRADE

Designed by FLOS Architectural, 2016



Recessed luminaire for direct lighting with LED. Elliptical lens 12°x52° incorporated.
Remote transformer not included

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Power (W)	26
Source flux (lm)	3146
Lumen Output (lm)	1536

Physical

Colour	White
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	42
Length (mm)	900
Net weight (kg)	0.92
Package volume (m3)	0.01
IP internal	20



Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)




IP

20

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **G**

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
Beam angle C0-180 (°)	12
Beam angle C90-270 (°)	12
Extreme cut off	No

Electrical

Insulation class	III
Frequency (Hz)	50/60
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable 1-10V, Dimmable DALI 1

Notes

18 LEDs.

Accessories & Power Supply

			
REQUIRED Power supply	REQUIRED Power supply	REQUIRED Power supply	REQUIRED Power supply
Electrical	Electrical	Electrical	Electrical
60.8515 Electronic transformer with constant voltage (24V) for LED. 60W. 100/240V. For independent use	60.9089 Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W	60.9407 Electronic transformer with constant voltage (24V) for LED. 100/240V. 120W	60.8703 Electronic transformer with constant voltage (24V) for LED. 100/240V. 25W
			
REQUIRED Accessory	REQUIRED Accessory	REQUIRED Accessory	OPTIONAL Accessory
06.1034.00	Electrical	Electrical	06.1032.00
Power cable L: 500 mm	60.8640 Control Unit 1-10V	60.9766 Control Unit DALI	Connection cable L: 100 mm



OPTIONAL
Accessory

06.1033.00

Connection cable L: 500 mm