

FA53605156-310 Matte Stainless Steel

## NEW

BOOK AN APPOINTMENT

|                   |                      |
|-------------------|----------------------|
| Mounting          | Ceiling recessed     |
| Environments      | Outdoor wet location |
| LED type          | LED array            |
| Number of lamps   | 1                    |
| Power (W)         | 38                   |
| System power (W)  | 40                   |
| Source flux (lm)  | 6637                 |
| Lumen Output (lm) | 3478                 |

|             |                       |
|-------------|-----------------------|
| Colour      | Matte Stainless Steel |
| Orientation | Fixed                 |
| IP internal | 66                    |
| IP external | 66                    |

Mounting instructions  ZIP

LDT / IES  ZIP2D  ZIP3D  ZIP


|    |    |
|----|----|
| IP | IK |
| 66 | 08 |

FA53605156-310

professional.flos.com | flos.outdoor@flos.com 1/3

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Photometric

|                    |            |
|--------------------|------------|
| Lighting type      | Direct     |
| Light distribution | Asymmetric |
| CCT (K)            | 4000       |
| CRI>               | 80         |
| Extreme cut off    | No         |

Electrical

|                    |                 |
|--------------------|-----------------|
| Insulation class   | II              |
| Frequency (Hz)     | 50-60           |
| Main voltage (Vac) | 220-240         |
| Power supply       | Remote included |
| Dimmable           | Yes             |
| Power supply type  | Dimmable 1-10V  |
| Emergency          | No              |

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

  Non-replaceable light source

  Replaceable control gear by an end-user

Accessories & Power Supply



REQUIRED  
Accessory

FA199  
Box for Ceiling Recessed  
Installation Leila 4




OPTIONAL  
Accessory

F990C00A000  
2 way terminal block 4 poles IP68  
H2O stop. (ø5,5÷12mm cable)



OPTIONAL  
Accessory

F990C010000  
3/4 way terminal block 4 poles  
IP68 H2O stop. (ø5,5÷12mm  
cable)



OPTIONAL  
Accessory

F990E00A000  
S.P.D. (SURGE PROTECTION  
DEVICE)