

FA53615601-310 White

Leila 4 White Painted Frame Dimmable 1-10V

NEW


Designed by FLOS Outdoor



LED source included. Integrated power supply 220-240V ON/OFF and dimmable 1-10V or DALI; remote kit with a 400mm cable section with watertight threaded M12 connector on the luminaire and a 250mm cable section for connection on the mains. This needs to be housed in the junction box for masonry ceilings (it needs to be ordered separately) or set next to the luminaire in case of plasterboard false ceilings. Dimmable version available upon request.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793678887
Mounting	Ceiling recessed
Environments	Outdoor wet location
LED type	LED array
Power (W)	38
System power (W)	40
Source flux (lm)	6111
Lumen Output (lm)	3443

Physical

Colour	White
Orientation	Fixed
Net weight (kg)	2.46
Package height (mm)	285
Package width (mm)	250
Package length (mm)	195
Package volume (m3)	0.01
IP internal	66
IP external	66

Download

Mounting instructions [ZIP](#)


Photometric Files

LDT / IES [ZIP](#)

Technical Drawings


2D [ZIP](#)

3D [ZIP](#)




Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable control gear by an end-user

Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	45
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Power supply type	Dimmable 1-10V
Emergency	No

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply




REQUIRED
Accessory

FA199
Box for Ceiling Recessed
Installation Leila 4



OPTIONAL
Accessory

F990C00A000
2 way terminal block 4 poles IP68
H20 stop. (ø5,5÷12mm cable)



OPTIONAL
Accessory

F990E00A000
S.P.D. (SURGE PROTECTION
DEVICE)



OPTIONAL
Accessory

F990C010000
3/4 way terminal block 4 poles
IP68 H20 stop. (ø5,5÷12mm
cable)