

FLOS

07.9641.14A9V Black

Light Bell Light Source 0-10V Dimmable

Designed by Piero Lissoni, 2017



Suspended luminaire for mounting on the ceiling with LED light source. (4 metres maximum distance to ceiling). Power supply source integrated into luminaire housing. Reflector not included; supplied separately.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	49.5
Source flux (lm)	5951
System flux (lm)	2635

Physical

Color	Black
Orientation	Fixed
Cord length (in)	157.48
Net weight (lb)	8.4
Package volume (in)	2014
IP internal	20



Download

Family spec sheet [ZIP](#)
Mounting instructions [ZIP](#)

Photometric Files


LDT / IES [ZIP](#)

Technical Drawings

2D [ZIP](#)
3D [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Roto symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	77

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	120-277
LED current (mA)	1400
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

Pin-block type dissipater. Please ask us for a higher IP. Includes a 4-meter suspension cable.

Integral LED is not field replaceable.

Wiring suitable for plenum spaces.

Canopy to cover j-box is provided separately.

3500K available, but not cataloged. Consult factory for additional color temperatures.

Light Bell Reflector + Light Bell Source must be ordered separately.

Accessories & Power Supply



REQUIRED
Accessory

07.9630.70

Light Bell Reflector



REQUIRED
Accessory

07.9630.76

Light Bell Reflector



REQUIRED
Accessory

07.9630.AN

Light Bell Reflector



REQUIRED
Accessory

07.9630.AP


Light Bell Reflector



REQUIRED
Accessory

07.9630.CE

Light Bell Reflector



REQUIRED
Accessory

08.8775.40

Rosette. IP20



REQUIRED
Accessory

F0556020

Light Bell Canopy Power supply
for standard and dimmable
versions



REQUIRED
Accessory

F0557020

Rosette for indoors. IP20.
Dimmable Push/Dali