



03.9410.14AUQ Black/White

## Light Shadow Adjustable No Trim 2 Spots Optic Medium - Non IC

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 2 LED lighting spots. Remote power supply.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 7                   |
| Source flux (lm)       | 570                 |
| System flux (lm)       | 470                 |

### Physical

|                          |             |
|--------------------------|-------------|
| Color                    | Black/White |
| Trim                     | No          |
| Orientation              | Adjustable  |
| Longitudinal tilting (°) | 30          |
| IP internal              | 20          |



### Download

|                       |                     |
|-----------------------|---------------------|
| Family spec sheet     | <a href="#">ZIP</a> |
| Mounting instructions | <a href="#">PDF</a> |
| Mounting instructions | <a href="#">PDF</a> |

### Photometric Files


|           |                     |
|-----------|---------------------|
| LDT / IES | <a href="#">ZIP</a> |
|-----------|---------------------|

### Technical Drawings

|    |                     |
|----|---------------------|
| 2D | <a href="#">ZIP</a> |
| 3D | <a href="#">ZIP</a> |



Schematic light drawing



Ecodesign and Energy Labelling



Photometric

|                          |                           |
|--------------------------|---------------------------|
| Lighting type            | Direct                    |
| Light distribution       | Symmetric                 |
| CCT (K)                  | 3000                      |
| CRI>                     | 90                        |
| McAdam steps (SDCM)      | 3                         |
| LED Life / Failure Ratio | L80B20 >50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 22                        |
| Beam angle C90-270 (°)   | 22                        |
| UGR <sub>L</sub>         | <10                       |

Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Forward voltage (V) | 7                                     |
| LED current (mA)    | 900                                   |
| Driver              | Integral - Splice Box                 |
| Dimmable            | Yes                                   |
| Dimming type        | Dimmable ELV, Dimmable 0-10V          |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply



REQUIRED  
Accessory


Installation

08.0515.00.90  
Pre-installation No Trim Frame 2L  
Adjustable




REQUIRED  
Power supply

SP20W900MA-120-C01  
Splice Box 9"x2.22"x1.25",  
900mA , 20W, 0-10V Dimmable,  
Thermal 120V




REQUIRED  
Power supply

SP20W900MA-277-C01  
Splice Box 9"x2.22"x1.25",  
900mA , 20W, 0-10V Dimmable,  
Thermal 277V



REQUIRED  
Power supply


SP20W900MA-ELV-C01  
Splice Box 9"x2.22"x1.25",  
900mA , 20W, ELV Dimmable,  
Thermal 120V



OPTIONAL  
Accessory

Installation

08.0059.90  
Accessory for mounting of No  
Trim Adjustable continuous line.



OPTIONAL  
Housing and Hanger Bar

TRAY-0031  
Registration Tray - non electrical,  
place holder for non IC new  
construction for Light Shadow  
Fixed 2 Light Trim