

03.8929.40AUQ White/Black

Light Shadow Adjustable No Trim 4 Spots Optic Spot - Non IC

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 4 LED lighting spots. Remote power supply.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	10.8
Source flux (lm)	1140
System flux (lm)	773

Physical

Color	White/Black
Trim	No
Orientation	Adjustable
Longitudinal tilting (°)	30
IP internal	20



Download

Family spec sheet	ZIP
Mounting instructions	PDF
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	10
Beam angle C90-270 (°)	10
UGR _L	<10

Electrical

Forward voltage (V)	12
LED current (mA)	900
Driver	Integral - Splice Box
Dimmable	Yes
Dimming type	Dimmable ELV, Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply




REQUIRED
Accessory

Installation

08.0516.00.90


Pre-installation No Trim Frame 4L
Fix Adjustable



REQUIRED
Power supply

SP20W900MA-ELV-C01


Splice Box 9"x2.22"x1.25",
900mA , 20W, ELV Dimmable,
Thermal 120V



REQUIRED
Power supply

SP25W900MA-120-A01


Splice Box 9"x3.59"x1.25",
900mA , 25W, 0-10V Dimmable,
Thermal 120V



REQUIRED
Power supply

SP25W900MA-277-A01

Splice Box 9"x3.59"x1.25",
900mA , 25W, 0-10V Dimmable,
Thermal 277V




OPTIONAL
Accessory

Installation

08.0059.90

Accessory for mounting of No
Trim Adjustable continuous line.



OPTIONAL
Housing and Hanger Bar

TRAY-0038

Registration Tray - non electrical,
place holder for non IC new
construction, for Light Shadow
Adjustable 4 Lights Trim