



03.7366.14AUQ Black/White

Light Shadow Adjustable No Trim 8 Spots Optic Wide Flood - Non IC

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	21.6
Source flux (lm)	2160
System flux (lm)	1763

Physical

Color	Black/White
Trim	No
Orientation	Adjustable
Longitudinal tilting (°)	30
IP internal	20



Download

Family spec sheet	ZIP
Mounting instructions	PDF
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	---------------------

Technical Drawings


2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy Labelling



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	45
UGR _L	<10

Electrical

Forward voltage (V)	24
LED current (mA)	900
Driver	Integral - Splice Box
Dimmable	Yes
Dimming type	Dimmable ELV, Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes

It requires a pre-installation frame, to be ordered separately.


Accessories & Power Supply



REQUIRED
Accessory


Installation

08.0517.00.90
Pre-installation No Trim Frame 8L
Fix Adjustable




REQUIRED
Power supply

SP25W900MA-120-A01
Splice Box 9"x3.59"x1.25",
900mA , 25W, 0-10V Dimmable,
Thermal 120V




REQUIRED
Power supply

SP25W900MA-277-A01
Splice Box 9"x3.59"x1.25",
900mA , 25W, 0-10V Dimmable,
Thermal 277V



REQUIRED
Power supply

SP30W900MA-ELV-U01
Splice Box 7"x3.59"x1.25", 900mA
, 30W, ELV Dimmable, Thermal
120V



OPTIONAL
Accessory

Installation

08.0059.90
Accessory for mounting of No
Trim Adjustable continuous line.