



03.7362.14ACB Black/White

## Light Shadow Adjustable No Trim Casambi Version 4 Spots Optic Wide Flood

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 10.8                |
| Source flux (lm)       | 1140                |
| Lumen Output (lm)      | 780                 |

### Physical

|                          |             |
|--------------------------|-------------|
| Colour                   | Black/White |
| Trim                     | No          |
| Orientation              | Adjustable  |
| Longitudinal tilting (°) | 30          |
| Recessed depth (mm)      | 75          |
| Length (mm)              | 149         |
| Net weight (kg)          | 0.34        |
| IP internal              | 20          |



### Download

|                       |                              |
|-----------------------|------------------------------|
| Mounting instructions | <a href="#">Download PDF</a> |
| Mounting instructions | <a href="#">Download PDF</a> |

### Photometric Files


|           |                              |
|-----------|------------------------------|
| LDT / IES | <a href="#">Download ZIP</a> |
|-----------|------------------------------|

### Technical Drawings

|     |                              |
|-----|------------------------------|
| 2D  | <a href="#">Download ZIP</a> |
| 3D  | <a href="#">Download ZIP</a> |
| Bim | <a href="#">Download ZIP</a> |



## Schematic light drawing



## Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

## Photometric

|                          |                           |
|--------------------------|---------------------------|
| Lighting type            | Direct                    |
| Light distribution       | Symmetric                 |
| CCT (K)                  | 3000                      |
| CRI>                     | 90                        |
| McAdam steps (SDCM)      | 3                         |
| LED Life / Failure Ratio | L80B20 >50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 45                        |
| Beam angle C90-270 (°)   | 45                        |
| Extreme cut off          | No                        |

## Electrical

|                                   |                  |
|-----------------------------------|------------------|
| Insulation class                  | II               |
| Frequency (Hz)                    | 50/60            |
| Main voltage (Vac)                | 220-240          |
| Alternating current voltage (Vac) | 230              |
| Power supply                      | Remote included  |
| Dimmable                          | Yes              |
| Power supply type                 | Dimmable Casambi |

## Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply




REQUIRED  
Frame

Installation

08.0516.00

Pre-installation No Trim Frame 4L  
Fix Adjustable



OPTIONAL  
Accessory

Installation

08.0059.90

Accessory for mounting of No  
Trim Adjustable continuous line.