

FLOS

05.1546.14ANI Black/Steel

Light Shadow Adjustable No Trim Mains Dimming Version 4 Spots Optic Spot

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	21.6
Source flux (lm)	1140
Lumen Output (lm)	800

Physical

Colour	Black/Steel
Trim	No
Orientation	Adjustable
Longitudinal tilting (°)	30
Recessed depth (mm)	75
Length (mm)	296
Net weight (kg)	0.5
IP internal	20



Download

Mounting instructions [PDF](#)

Mounting instructions [PDF](#)

Photometric Files

LDT / IES [ZIP](#)

Technical Drawings


2D [ZIP](#)

3D [ZIP](#)

Bim [ZIP](#)




Schematic light drawing




Beam Angle: 13°		
h(m)	E(k)	D(m)
1	9431	0.23
2	2358	0.45
3	1048	0.68
4	590	0.90
5	378	1.13

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	12
Beam angle C90-270 (°)	12
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Mains Cut Dimming

Notes

Pre-Installation frame not required.

Accessories & Power Supply




REQUIRED Frame

Installation

08.0516.00

Pre-installation No Trim Frame 4L
Fix Adjustable



OPTIONAL Accessory

Installation

08.0059.90

Accessory for mounting of No
Trim Adjustable continuous line.