

# FLOS

03.8379.14A Black/Black

## Light Shadow Fixed No Trim 12 Spots Optic Wide Flood

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	32.4
Source flux (lm)	3420
Lumen Output (lm)	2815

### Physical

Colour	Black/Black
Trim	No
Orientation	Fixed
Recessed depth (mm)	75
Length (mm)	420
Net weight (kg)	0.66
IP internal	20
IP external	55



### Download

Mounting instructions [PDF](#)

Mounting instructions [PDF](#)

### Photometric Files

LDT / IES [ZIP](#)

### Technical Drawings


2D [ZIP](#)

3D [ZIP](#)

BIM [ZIP](#)




## Schematic light drawing




Luminous flux luminaire  
2815 lm (EXTREME CUT OFF)

Beam Angle:	46°
h(m)	E(k)
1	5339
2	1335
3	593
4	334
5	214
	0.84
	1.69
	2.53
	3.38
	4.22

## Ecodesign and Energy Labelling



Replaceable (LED only)  
light source by a  
professional



Replaceable control  
gear by a professional

## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	45
UGR <sub>L</sub>	<10

## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Alternating current voltage (Vac)	230
Power supply	Remote included
Dimmable	No
Power supply type	Non Dimmable

## Notes

It requires a pre-installation frame, to be ordered separately.

## Accessories & Power Supply




### REQUIRED Frame

#### Installation

08.0513.00

Pre-installation No Trim Frame  
12L Fix



### OPTIONAL Accessory

#### Installation

08.0052.90

Accessory for mounting of No  
Trim Fix continuous line.