



03.8350.14AUQ Black/White

# **Light Shadow Fixed No Trim 2 Spots Optic Wide Flood - Non IC**

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 2 LED lighting spots. Remote power supply.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

# Physical

Mounting	Ceiling recessed	
Environments	Indoor dry location	
Light Source Type	ource Type LED	
Light sources included	Yes	
LED type	Power LED	
Lamp category LED		
Number of lamps	1	
Power (W)	7	
Source flux (lm)	540	
System flux (lm)	443	

Main specifications

Color	Black/White	
Trim	No	
Orientation	Fixed	
IP internal	20	
IP external	55	



Download	
Family spec sheet	<b>业</b> ZIP
Mounting instructions	<b>业</b> PDF
Photometric Files LDT/IES	<b>⊥</b> ZIP

















https://professional.flos.com/en-US/us/product/light-shadow-fixed-no-trim-2-spots-optic-wide-flood-non-ic-03.8350.14auq/

03.8350.14AUQ

# Schematic light drawing



Beam Angle:		46°
h(m)	E(lx)	D(m)
1	841	0.84
2	210	1.69
3	93	2.53
4	53	3.38
5	34	4.22

Luminous flux luminaire 443 lm (EXTREME CUT OFF)

## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	45
	73
Beam angle C90-270 (°)	45

#### Electrical

Forward voltage (V)	7
LED current (mA)	900
Driver	Integral - Splice Box
Dimmable	Yes
Dimming type	Dimmable ELV, Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)

#### Notes

It requires a pre-installation frame, to be ordered separately.









REQUIRED Frame

Installation

08.0510.00.90

Light Shadow 2 Spots 5/8" Frame Fixed Trimless

#### REQUIRED Power supply

SP20W900MA-120-C01

Splice Box 9"x2.22"x1.25", 900mA , 20W, 0-10V Dimmable, Thermal 120V

#### REQUIRED Power supply

SP20W900MA-277-C0

Splice Box 9"x2.22"x1.25", 900mA , 20W, 0-10V Dimmable, Thermal 277V

#### REQUIRED Power supply

SP20W900MA-FLV-CO

Splice Box 9"x2.22"x1.25", 900mA , 20W, ELV Dimmable, Thermal 120V



## OPTIONAL Accessory

Installation

08.0052.90

Accessory for mounting of No Trim Fix continuous line.



#### OPTIONAL Housing and Hanger Bar

TRAY-0032

Registration Tray - non electrical, place holder for non IC new construction, for Light Shadow Fix 2 Lights Trimless Fixed 2 Lights Trimless