

## Light Shadow Fixed No Trim 4 Spots Optic Wide Flood


Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 10.8                |
| Source flux (lm)       | 1080                |
| Lumen Output (lm)      | 731                 |

### Physical

|                     |             |
|---------------------|-------------|
| Colour              | White/White |
| Trim                | No          |
| Orientation         | Fixed       |
| Recessed depth (mm) | 75          |
| Length (mm)         | 140         |
| Net weight (kg)     | 0.34        |
| IP internal         | 20          |
| IP external         | 55          |

### Download

|                       |                       |
|-----------------------|-----------------------|
| Mounting instructions | <a href="#">↓ PDF</a> |
| Mounting instructions | <a href="#">↓ PDF</a> |

### Photometric Files


|           |                       |
|-----------|-----------------------|
| LDT / IES | <a href="#">↓ ZIP</a> |
|-----------|-----------------------|

### Technical Drawings

|     |                       |
|-----|-----------------------|
| 2D  | <a href="#">↓ ZIP</a> |
| 3D  | <a href="#">↓ ZIP</a> |
| Bim | <a href="#">↓ ZIP</a> |



## Schematic light drawing



## Ecodesign and Energy Labelling



## Photometric

|                          |                           |
|--------------------------|---------------------------|
| Lighting type            | Direct                    |
| Light distribution       | Symmetric                 |
| CCT (K)                  | 2700                      |
| CRI>                     | 90                        |
| McAdam steps (SDCM)      | 3                         |
| LED Life / Failure Ratio | L80B20 >50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 45                        |
| Beam angle C90-270 (°)   | 45                        |
| UGR <sub>L</sub>         | <16                       |


## Electrical

|                                   |                 |
|-----------------------------------|-----------------|
| Insulation class                  | II              |
| Frequency (Hz)                    | 50/60           |
| Main voltage (Vac)                | 220-240         |
| Alternating current voltage (Vac) | 230             |
| Power supply                      | Remote included |
| Dimmable                          | No              |
| Power supply type                 | Non Dimmable    |

## Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply



REQUIRED  
Frame

Installation

08.0511.00

Pre-installation No Trim Frame 4L  
Fix



OPTIONAL  
Accessory

Installation

08.0052.90

Accessory for mounting of No  
Trim Fix continuous line.