




05.0642.40 White/Bronze

# **Light Shadow Fixed No Trim 4 Spots Square Optic Spot NEW**

Designed by FLOS Architectural, 2022



841lm - 2700K - CRI> 90 - Beam° 11

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V). It requires a pre-installation frame, to be ordered separately.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

## Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
System power (W)	10.8
Source flux (lm)	0
Lumen Outnut (lm)	8/11

## Physical

Colour	White/Bronze
Trim	No
Orientation	Fixed
Net weight (kg)	0.34
Package height (mm)	16
Package width (mm)	14
Package length (mm)	21
IP internal	20
IP external	55



## Download

Mounting instructions



# Photometric Files

LDT / IES



# **Technical Drawings**

2D	<b>业</b> ZIP
3D	<b>⊥</b> ZIP









https://professional.flos.com/en/global/product/light-shadow-fixed-no-trim-4-spots-square-optic-spot-05.0642.40/

05.0642.40

# Schematic light drawing



Ве	am	Angle:	12
h(n	n)	E(lx)	D(r
1	1	3375	0.2
2		3344	0.4
3		1486	0.6
4		836	0.8
5		535	1.0

Luminous flux luminaire 841 lm (EXTREME CUT OFF)

Ве	am ,	Angle:	: 12
h(n	n)	E(lx)	D(n
1	13	375	0.2
2	3	344	0.4
3	1	486	0.6
4		836	0.8
5		535	1.0

# **Ecodesign and Energy** Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

#### Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
LED Life / Failure Ratio	L80B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	11
Beam angle C90-270 (°)	11
UGR <sub>L</sub>	<10

#### Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
LED current (mA)	900
Power supply	Remote included
Dimmable	No
Power supply type	Non Dimmable

# **Accessories & Power Supply**





REQUIRED Frame

08.0269.00

Pre-installation frame for Light Shadow Fixed No Trim 4 Spots Square

#### OPTIONAL

08 0270 00

Accessory for mounting of No Trim continuous line for Light Shadow Fixed 4 Spots Square