

Light Shadow Fixed No Trim Casambi Version 4 Spots Optic Wide Flood


Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Ceiling recessed |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 10.4 |
| System power (W) | 10.8 |
| Source flux (lm) | 1080 |
| Lumen Output (lm) | 735 |

Physical

| | |
|---------------------|-------------|
| Colour | Black/Black |
| Trim | No |
| Orientation | Fixed |
| Recessed depth (mm) | 75 |
| Length (mm) | 140 |
| Net weight (kg) | 0.34 |
| IP internal | 20 |
| IP external | 55 |

Download

| | |
|-----------------------|-----------------------|
| Mounting instructions | ↓ PDF |
| Mounting instructions | ↓ PDF |

Photometric Files


| | |
|-----------|-----------------------|
| LDT / IES | ↓ ZIP |
|-----------|-----------------------|

Technical Drawings

| | |
|-----|-----------------------|
| 2D | ↓ ZIP |
| 3D | ↓ ZIP |
| Bim | ↓ ZIP |



Schematic light drawing



Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Photometric

| | |
|--------------------------|---------------------------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| McAdam steps (SDCM) | 3 |
| LED Life / Failure Ratio | L80B20 >50.000h (Tc=85°C) |
| Beam angle C0-180 (°) | 45 |
| Beam angle C90-270 (°) | 45 |
| Extreme cut off | No |
| UGR _L | <10 |

Electrical


| | |
|-----------------------------------|------------------|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Alternating current voltage (Vac) | 230 |
| LED current (mA) | 900 |
| Power supply | Remote included |
| Dimmable | Yes |
| Power supply type | Dimmable Casambi |

Notes

It requires a pre-installation frame, to be ordered separately.

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Accessories & Power Supply




REQUIRED
Frame

Installation

08.0511.00

Pre-installation No Trim Frame 4L
Fix



OPTIONAL
Accessory

Installation

08.0052.90

Accessory for mounting of No
Trim Fix continuous line.