

## Light Shadow Fixed No Trim Casambi Version 8 Spots Optic Wide Flood


Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	20.9
System power (W)	21.6
Source flux (lm)	2160
Lumen Output (lm)	1763

### Physical

Colour	White/White
Trim	No
Orientation	Fixed
Recessed depth (mm)	75
Length (mm)	280
Net weight (kg)	0.5
IP internal	20
IP external	55

### Download

Mounting instructions	<a href="#">Download PDF</a>
Mounting instructions	<a href="#">Download PDF</a>

### Photometric Files


LDT / IES	<a href="#">Download ZIP</a>
-----------	------------------------------

### Technical Drawings



2D	<a href="#">Download ZIP</a>
3D	<a href="#">Download ZIP</a>
Bim	<a href="#">Download ZIP</a>



Schematic light drawing



### Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	45
Extreme cut off	No
UGR <sub>L</sub>	<16

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Alternating current voltage (Vac)	230
LED current (mA)	900
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmable Casambi

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply




REQUIRED  
Frame

Installation

08.0512.00

Pre-installation No Trim Frame 8L  
Fix



OPTIONAL  
Accessory

Installation

08.0052.90

Accessory for mounting of No  
Trim Fix continuous line.