

FLOS

03.8378.14ANI Black/White

Light Shadow Fixed No Trim Mains dimming Version 12 Spots Optic Wide Flood

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

| | |
|------------------------|---------------------|
| Mounting | Ceiling recessed |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 31.3 |
| System power (W) | 32.4 |
| Source flux (lm) | 2712 |
| Lumen Output (lm) | 2232 |
| Efficacy (lm/W) | 82 |

Physical

| | |
|---------------------|-------------|
| Colour | Black/White |
| Trim | No |
| Orientation | Fixed |
| Recessed depth (mm) | 75 |
| Length (mm) | 420 |
| Net weight (kg) | 0.66 |
| IP internal | 20 |
| IP external | 55 |



Download

Mounting instructions [PDF](#)

Mounting instructions [PDF](#)

Photometric Files

LDT / IES [ZIP](#)

Technical Drawings


2D [ZIP](#)

3D [ZIP](#)


Bim [ZIP](#)



Schematic light drawing



Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

| | |
|--------------------------|---------------------------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 90 |
| McAdam steps (SDCM) | 3 |
| LED Life / Failure Ratio | L80B20 >50.000h (Tc=85°C) |
| Beam angle C0-180 (°) | 45 |
| Beam angle C90-270 (°) | 47 |
| Extreme cut off | No |
| UGR _L | <10 |

Electrical

| | |
|-----------------------------------|-------------------|
| Insulation class | II |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-240 |
| Alternating current voltage (Vac) | 230 |
| LED current (mA) | 900 |
| Power supply | Remote included |
| Dimmable | Yes |
| Power supply type | Mains Cut Dimming |

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply



REQUIRED
Frame

Installation

08.0513.00

Pre-installation No Trim Frame
12L Fix



OPTIONAL
Accessory

Installation

08.0052.90

Accessory for mounting of No
Trim Fix continuous line.