

# FLOS



03.8367.14ANI Black/Black

## Light Shadow Fixed No Trim Mains dimming Version 8 Spots Optic Wide Flood

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 20.9                |
| System power (W)       | 21.6                |
| Source flux (lm)       | 1760                |
| Lumen Output (lm)      | 1441                |
| Efficacy (lm/W)        | 80                  |

### Physical

|                     |             |
|---------------------|-------------|
| Colour              | Black/Black |
| Trim                | No          |
| Orientation         | Fixed       |
| Recessed depth (mm) | 75          |
| Length (mm)         | 280         |
| Net weight (kg)     | 0.5         |
| IP internal         | 20          |
| IP external         | 55          |



### Download

Mounting instructions [Download PDF](#)

Mounting instructions [Download PDF](#)

### Photometric Files

LDT / IES [Download ZIP](#)

### Technical Drawings


2D [Download ZIP](#)

3D [Download ZIP](#)

[Bim](#) [Download ZIP](#)



Schematic light drawing



### Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Photometric

|                          |                           |
|--------------------------|---------------------------|
| Lighting type            | Direct                    |
| Light distribution       | Symmetric                 |
| CCT (K)                  | 2700                      |
| CRI>                     | 90                        |
| McAdam steps (SDCM)      | 3                         |
| LED Life / Failure Ratio | L80B20 >50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 46                        |
| Beam angle C90-270 (°)   | 47                        |
| Extreme cut off          | No                        |
| UGR <sub>L</sub>         | <10                       |

Electrical

|                                   |                   |
|-----------------------------------|-------------------|
| Insulation class                  | II                |
| Frequency (Hz)                    | 50/60             |
| Main voltage (Vac)                | 220-240           |
| Alternating current voltage (Vac) | 230               |
| LED current (mA)                  | 900               |
| Power supply                      | Remote included   |
| Dimmable                          | Yes               |
| Power supply type                 | Mains Cut Dimming |

Notes

It requires a pre-installation frame, to be ordered separately.

Accessories & Power Supply




REQUIRED  
Frame

Installation

08.0512.00

Pre-installation No Trim Frame 8L  
Fix



OPTIONAL  
Accessory

Installation

08.0052.90

Accessory for mounting of No  
Trim Fix continuous line.