

## Light Shadow Fixed Trim 2 Spots Optic Wide Flood - Non IC

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 2 LED lighting spots. Remote power supply.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| Power (W)              | 7                   |
| Source flux (lm)       | 540                 |
| System flux (lm)       | 441                 |

### Physical

|             |             |
|-------------|-------------|
| Color       | White/White |
| Trim        | Yes         |
| Orientation | Fixed       |
| IP internal | 20          |
| IP external | 55          |



### Download

Family spec sheet [ZIP](#)

Mounting instructions [PDF](#)

### Photometric Files

LDT / IES [ZIP](#)




### Ecodesign and Energy Labelling

 Replaceable (LED only) light source by a professional

 Replaceable control gear by a professional

Schematic light drawing



Photometric

|                          |                              |
|--------------------------|------------------------------|
| Lighting type            | Direct                       |
| Light distribution       | Symmetric                    |
| CCT (K)                  | 2700                         |
| CRI>                     | 90                           |
| LED Life / Failure Ratio | L80B20 >50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 45                           |
| Beam angle C90-270 (°)   | 45                           |
| UGR <sub>L</sub>         | <10                          |


Electrical

|                     |                                          |
|---------------------|------------------------------------------|
| Forward voltage (V) | 7                                        |
| LED current (mA)    | 900                                      |
| Driver              | Integral - Splice Box                    |
| Dimmable            | Yes                                      |
| Dimming type        | Dimmable ELV,<br>Dimmable 0-10V          |
| Dimming interface   | Remote Dimmable<br>(Dimmer Not Included) |

Notes


Pre-installation frame not required.

Accessories & Power Supply




REQUIRED  
Power supply

SP20W900MA-120-C01  
Splice Box 9"x2.22"x1.25",  
900mA , 20W, 0-10V Dimmable,  
Thermal 120V




REQUIRED  
Power supply

SP20W900MA-277-C01  
Splice Box 9"x2.22"x1.25",  
900mA , 20W, 0-10V Dimmable,  
Thermal 277V



REQUIRED  
Power supply

SP20W900MA-ELV-C01  
Splice Box 9"x2.22"x1.25",  
900mA , 20W, ELV Dimmable,  
Thermal 120V



OPTIONAL  
Housing and Hanger Bar

TRAY-0032  
Registration Tray - non electrical,  
place holder for non IC new  
construction, for Light Shadow Fix  
2 Lights Trimless Fixed 2 Lights  
Trimless