

Light Shadow Fixed Trim 2 Spots Optic Wide Flood - Non IC

Designed by FLOS Architectural, 2022



Recessed integrated luminaire with 2 LED lighting spots. Remote power supply.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	7
Source flux (lm)	540
System flux (lm)	464

Physical

Color	White/Black
Trim	Yes
Orientation	Fixed
IP internal	20
IP external	55



Download


Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)

Photometric Files


LDT / IES [ZIP](#)



Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L80B20 >50.000h (Tc=85°C)
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	45
UGR _L	<10


Electrical

Forward voltage (V)	7
LED current (mA)	900
Driver	Integral - Splice Box
Dimmable	Yes
Dimming type	Dimmable ELV, Dimmable 0-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)

Notes


Pre-installation frame not required.

Accessories & Power Supply




REQUIRED
Power supply

SP20W900MA-120-C01
Splice Box 9"x2.22"x1.25",
900mA , 20W, 0-10V Dimmable,
Thermal 120V




REQUIRED
Power supply

SP20W900MA-277-C01
Splice Box 9"x2.22"x1.25",
900mA , 20W, 0-10V Dimmable,
Thermal 277V



REQUIRED
Power supply

SP20W900MA-ELV-C01
Splice Box 9"x2.22"x1.25",
900mA , 20W, ELV Dimmable,
Thermal 120V



OPTIONAL
Housing and Hanger Bar

TRAY-0032
Registration Tray - non electrical,
place holder for non IC new
construction, for Light Shadow Fix
2 Lights Trimless Fixed 2 Lights
Trimless