



05.1811.40A9V White/Steel

Light Shadow Optic Medium 0-10V Dimmable



10.8W - 827lm - 2700K - CRI> 90 - Beam° 20

LED lighting module, with 4 spotlights and low glare, to be installed in the The Running Magnet system. DC/DC, built-in electronic current converter.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT





Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
LED type	Power LED
Number of lamps	1
Power (W)	10.8
Source flux (lm)	1080
System flux (lm)	827

Physical

Color	White/Steel
Trim	No
Orientation	Fixed
Net weight (lb)	0.75
Package volume (in)	62
IP internal	20

Download	
Family spec sheet	₹ ZIF
Mounting instructions	↓ PDF
Photometric Files	

Photometric Files

LDT / IES















https://professional.flos.com/en-US/us/product/light-shadow-optic-medium-0-10v-dimmable-05.1811.40a9v/

05.1811.40A9V

Schematic light drawing



Beam Angle:		21°
h(m)	E(lx)	D(m)
1	6094	0.36
2	1523	0.73
3	677	1.09
4	381	1.45
5	244	1.81

Luminous flux luminaire 827 lm (EXTREME CUT OFF)

Photometric

Light distribution	Roto symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	20
Beam angle C90-270 (°)	20
UGR _L	<10

Electrical

Insulation class	II
Forward voltage (V)	24
LED current (mA)	900
Dimmable	Yes
Dimming type	Dimmable 0-10V