

Light Shadow Pro Ø45 Push Spot - IC Rated NEW


Designed by FLOS Architectural, 2022



Luminaire with 2x1 functionality: it can work as downlight (recessed, flush with ceiling) or as a projector (fully adjustable). The passage from one position to the other can be made by moving the product easily by hand. Necessary installation pre-frames, not included (to be ordered separately). Requires a power supply unit which is not included, to be ordered separately according to recommendations.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| EAN | Valencia |
| Mounting | Ceiling recessed |
| Environments | Indoor dry location |
| Light Source Type | LED |
| Light sources included | Yes |
| LED type | LED array |
| Lamp category | LED |
| Number of lamps | 1 |
| Power (W) | 6 |
| System power (W) | 8.2 |
| Source flux (lm) | 643 |
| System flux (lm) | 523 |

Physical

| | |
|---------------------|-------------------|
| Color | Black/Steel/Black |
| Trim | No |
| Orientation | Adjustable |
| Recessed depth (in) | 5.91 |
| Net weight (lb) | 0.51 |
| IP internal | 20 |
| IP external | 20 |

Download

| | |
|-----------------------|---------------------|
| Family spec sheet | ZIP |
| Mounting instructions | PDF |
| Mounting instructions | PDF |


Photometric Files

| | |
|-----------|---------------------|
| LDT / IES | ZIP |
|-----------|---------------------|

Technical Drawings

| | |
|----|---------------------|
| 2D | ZIP |
| 3D | ZIP |

Schematic light drawing



Photometric


| | |
|--------------------------|-----------------------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 2700 |
| CRI> | 90 |
| McAdam steps (SDCM) | 3 |
| LED Life / Failure Ratio | L80B50>60.000h_Tc85°C |
| Beam angle C0-180 (°) | 15 |
| Beam angle C90-270 (°) | 15 |
| Extreme cut off | Yes |
| UGR _L | <10 |

Electrical

| | |
|---------------------|---------------------------------------|
| Forward voltage (V) | 12 |
| LED current (mA) | 500 |
| Driver | Remote |
| Dimmable | Yes |
| Dimming interface | Remote Dimmable (Dimmer Not Included) |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **G**



Notes

Light Shadow Push can be placed in top position, functioning as a downlight (perfectly flush to ceiling), or in bottom position, functioning as an adjustable spotlight. IC Rated- Inherently protected. Ceiling recessed IC-rated - Mud-in


Accessories & Power Supply



REQUIRED
Frame

08.0757.00.9S

Installation Frame No Trim Light
Shadow Pro Ø45 Push



REQUIRED
Power supply

Electrical

SP12W500MA-10V-T01

Splice Box UL 7"x3-5/8"x1-1/4",
UL With Eldoled Eco Drive 12W
series Driver Programmed to
500mA , 0-10V Dim 120-277V