

# FLOS

03.8957.40AQF White/White/Black

## Light Shadow Surface 4 Spots Optic Spot

Designed by FLOS Architectural




10.8W - 1080lm - 2700K - CRI> 90 - Beam° 10

Surface luminaire with 4 LED lighting spots. Power source incorporated.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Power (W)              | 10.8                |
| System power (W)       | 14                  |
| System flux (lm)       | 1080                |

### Physical

|                 |                   |
|-----------------|-------------------|
| Color           | White/White/Black |
| Orientation     | Fixed             |
| Net weight (lb) | 1.33              |
| IP internal     | 44                |

### Download

Family spec sheet [ZIP](#)


Mounting instructions [PDF](#)

### Photometric Files


LDT / IES [ZIP](#)



### Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

## Photometric

|                          |                           |
|--------------------------|---------------------------|
| Lighting type            | Direct                    |
| Light distribution       | Symmetric                 |
| CCT (K)                  | 2700                      |
| CRI>                     | 90                        |
| LED Life / Failure Ratio | L80B20 >50.000h (Tc=85°C) |
| Beam angle C0-180 (°)    | 10                        |
| Beam angle C90-270 (°)   | 10                        |
| UGR <sub>L</sub>         | <10                       |

## Electrical

|                     |                                       |
|---------------------|---------------------------------------|
| Frequency (Hz)      | 50/60                                 |
| Main voltage (Vac)  | 120                                   |
| Forward voltage (V) | 12                                    |
| LED current (mA)    | 900                                   |
| Driver              | Integrated                            |
| Dimmable            | Yes                                   |
| Dimming type        | Mains Cut Dimming                     |
| Dimming interface   | Remote Dimmable (Dimmer Not Included) |


## Accessories & Power Supply



REQUIRED

08.0252.14.19

Surface Spacer



REQUIRED

08.0252.40.19

Surface Spacer