

FLOS



03.8965.14A Black/Black/Black

Light Shadow Surface 4 Spots Optic Spot

Designed by FLOS Architectural




LED - Power LED - 10.8W - 724lm - 2700K - CRI> 90 - Beam° 10

Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	1
Power (W)	10.8
Source flux (lm)	1080
Lumen Output (lm)	724

Physical

Colour	Black/Black/Black
Trim	No
Orientation	Fixed
Length (mm)	146
Net weight (kg)	0.80
IP internal	44

Download

Mounting instructions  PDF

Item information  JPG

Photometric Files


LDT / IES  ZIP

Technical Drawings

 Bim  ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	10
Beam angle C90-270 (°)	10
UGR _L	<10

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Alternating current voltage (Vac)	230
Power supply	Integrated
Dimmable	No
Power supply type	Non Dimmable
Emergency	No