

FLOS

05.2360.14ADA Steel/Black/Black

Light Shadow Surface Dali Version 4 Spots Optic Flood NEW

Designed by FLOS Architectural




LED - Power LED - 10.8W - 829lm - 2700K - CRI> 90 - Beam° 33

Surface luminaire with 4 LED lighting spots. Power source 220-240V incorporated.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Surface
Environments	Indoor dry location
LED type	Power LED
Lamp category	LED
Number of heads	1
Power (W)	10.8
Source flux (lm)	1080
System flux (lm)	829

Physical

Colour	Steel/Black/Black
Orientation	Fixed
Length (mm)	146
Net weight (kg)	0.8
Package height (cm)	6
Package width (cm)	13
Package length (cm)	21
IP internal	44

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	2591	0.60
2	648	1.19
3	288	1.79
4	162	2.39
5	104	2.99

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
LED Life / Failure Ratio	L80B50
Beam angle C0-180 (°)	33
Beam angle C90-270 (°)	34

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220
Alternating current voltage (Vac)	230
Forward voltage (V)	12
LED voltage Vf (Vdc)	12
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable DALI 1

Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional