

# FLOS

03.2264.14 Black

## Light Stripe Diffused NEW

Designed by FLOS Architectural, 2020




LED - Top LED - 9W - 411lm - 2700K - CRI> 90 - Beam° 114

Diffused LED light module to be installed in The Micro Running Magnet System.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
LED type	Top LED
Lamp category	LED
Number of heads	1
Power (W)	9
System power (W)	11
Source flux (lm)	410
System flux (lm)	411
Efficacy (lm/W)	37.36

### Physical

Colour	Black
Orientation	Fixed
Length (mm)	600
Net weight (kg)	0.09
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings

3D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim




### Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional

## Schematic light drawing



### Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	114
Beam angle C90-270 (°)	135

### Electrical

Insulation class	III
Main voltage (Vac)	
Forward voltage (V)	24
LED voltage Vf (Vdc)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)