

FLOS

03.2275.14 Black

Light Stripe Diffused NEW

Designed by FLOS Architectural, 2020




LED - Top LED - 18W - 904lm - 5000K - CRI> 90 - Beam° 114

Diffused LED light module to be installed in The Micro Running Magnet System.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	18
System power (W)	23.5
Source flux (lm)	904
Lumen Output (lm)	904
Efficacy (lm/W)	38.47

Physical

Colour	Black
Orientation	Fixed
Length (mm)	1200
Net weight (kg)	0.09
IP internal	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

3D [↓ ZIP](#)


[Bim](#) [↓ ZIP](#)



Ecodesign and Energy Labelling



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	5000
CRI>	90
McAdam steps (SDCM)	2
LED Life / Failure Ratio	L90B10>100.000h (Tc=71°C)
Beam angle C0-180 (°)	114
Beam angle C90-270 (°)	135

Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)