

FLOS

03.2283.14 Black

Light Stripe Wall-Washer NEW

Designed by FLOS Architectural, 2020




LED - Top LED - 4.5W - 204lm - 5000K - CRI> 90 - Beam° 114

Asymmetric wall-washer LED light module to be installed in The Micro Running Magnet System.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	4.5
System power (W)	5
Source flux (lm)	204
System flux (lm)	204
Efficacy (lm/W)	40.8

Physical

Color	Black
Orientation	Fixed
Length (in)	11.82
Net weight (lb)	0.2
IP internal	20

Download

- [Family spec sheet](#) ZIP
- [Mounting instructions](#) PDF

Photometric Files

- [LDT / IES](#) ZIP


Technical Drawings

- [2D](#) ZIP
- [3D](#) ZIP

Ecodesign and Energy Labelling



Schematic light drawing



Beam Angle:		
h(m)	E(lx)	D(m)
1	3	
2	5	
3	12	
4	46	
5	0	

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	5000
CRI>	90
McAdam steps (SDCM)	2
LED Life / Failure Ratio	L90B10>100.000h (Tc=71°C)
Beam angle C0-180 (°)	114
Beam angle C90-270 (°)	135

Electrical

Insulation class	III
Forward voltage (V)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)