

# FLOS

03.2295.14 Black

## Light Stripe Wall-Washer NEW

Designed by FLOS Architectural, 2020




LED - Top LED - 18W - 815lm - 5000K - CRI> 90 - Beam° 114

Asymmetric wall-washer LED light module to be installed in The Micro Running Magnet System.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Top LED
Lamp category	LED
Number of lamps	1
Power (W)	18
System power (W)	23.5
Source flux (lm)	815
Lumen Output (lm)	815
Efficacy (lm/W)	34.68

### Physical

Colour	Black
Orientation	Fixed
Length (mm)	1200
Net weight (kg)	0.09
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

### Technical Drawings


3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)

### Ecodesign and Energy Labelling



## Schematic light drawing



Beam Angle:		
h(m)	E(lx)	D(m)
1	12	
2	20	
3	46	
4	184	
5	0	

### Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	5000
CRI>	90
McAdam steps (SDCM)	2
LED Life / Failure Ratio	L90B10>100.000h (Tc=71°C)
Beam angle C0-180 (°)	114
Beam angle C90-270 (°)	135

### Electrical

Insulation class	III
Forward voltage (V)	24
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Non Dimmable, Dimmable
Dimming interface	Remote Dimmable (Dimmer Not Included)