

FLOS

03.6813.3BBDA White/White

Light Supply Wall-Washer Trim Dimmable

Designed by FLOS Architectural, 2017


LED - LED array - 33.2W - 1845lm - 4000K - CRI> 90 - Beam° 36



Recessed luminaire with LED light source. Remote 220/240V power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	33.2
Source flux (lm)	3506
System flux (lm)	1845

Physical

Colour	White/White
Trim	No
Orientation	Fixed
Recessed depth (mm)	290
Net weight (kg)	1.01
IP internal	20
IP external	44

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Beam Angle: 36°

h(m)	E(lx)	D(m)
1	2179	0.74
2	545	1.48
3	242	2.22
4	136	2.95
5	87	3.69

Luminous flux luminaire
1845 lm (EXTREME CUT OFF)

Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	90
Beam angle C0-180 (°)	36
Beam angle C90-270 (°)	51
Extreme cut off	No

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmable DALI 2